



Beam Angle (Full): 38°



Distance (mm)	Beam Diameter (mm)	Illuminance (lx)
0.5	0.32	7466
1.0	0.45	1867
1.5	0.67	830
2.0	0.89	467
2.5	1.12	298
3.0	1.34	207

Product Description

Simple and Classic recessed COB round Downlight luminaire , Die-cast Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

嵌入式COB筒灯，压铸式铝合金外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐蚀性。



Product Name/产品名称	FR1002	
Dimension/尺寸	ø 70mm*38mm	
Lamp Source/光源	CREE COB (Bridgelux / CITIZEN Optional)	
Wattage/瓦数	5W	7W
Luminous Flux/光通量	400 Lumen	510 Lumen
Luminaire Efficacy/光效	80 Lumen / Watt	72 Lumen / Watt
Color Temperature/色温	2700K, 3000K, 4000K, 5000K	
CRI/显色指数	>80 (over 90 optional)	
Dimming Method/调光方式	Triac, 0-10V, Dali	
Beam Angle/光束角	20° / 30° / 50°	
Cut Hole Size/开孔尺寸	ø 60mm	
Reflector Colour/反光杯颜色	Silver	
Available Color/外壳颜色	White, Black	
Shell material/外壳材质	Aluminum	
IP Rating/防护等级	IP20	
Certification/证书	CE	