



Beam Angle (Full): 24°



Distance (ft)	Core Diameter (ft)	Illuminance (ft)
0.5	0.38	10718
1.0	0.38	2679
1.5	0.57	1181
2.0	0.76	670
2.5	0.95	429
3.0	1.14	298

### Product Description

Recessed COB round Downlight luminaire , Die-cast Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . Designed and equipped with anti-glare reflector.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

嵌入式COB筒灯，压铸式铝合金外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐蚀性。



<b>Product Name/产品名称</b>	FR1013	
<b>Dimension/尺寸</b>	∅ 105mm*68mm	
<b>Lamp Source/光源</b>	CREE COB (Bridgelux / CITIZEN Optional)	
<b>Wattage/瓦数</b>	15W	18W
<b>Luminous Flux/光通量</b>	1310 Lumen	1560 Lumen
<b>Luminaire Efficacy/光效</b>	87 Lumen / Watt	86 Lumen / Watt
<b>Color Temperature/色温</b>	2700K, 3000K, 4000K, 5000K	
<b>CRI/显色指数</b>	>80 (over 90 optional)	
<b>Dimming Method/调光方式</b>	Triac, 0-10V, Dali	
<b>Beam Angle/光束角</b>	15° / 24° / 50°	
<b>Cut Hole Size/开孔尺寸</b>	∅ 98mm	
<b>Reflector Colour/反光杯颜色</b>	Silver	
<b>Available Color/外壳颜色</b>	White, Black	
<b>Shell material/外壳材质</b>	Aluminum	
<b>IP Rating/防护等级</b>	IP20	
<b>Certification/证书</b>	CE	

# FR1013