



Beam Angle (Full): 90.6°

0.5	1.01	1514
1.0	2.02	329
1.5	3.03	168
2.0	4.04	95
2.5	5.05	61
3.0	6.06	42



Distance (m) Core Diameter (m) Illuminance (lx)

Product Description

Recessed Downlight luminaire ,Die-cast Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . Designed and equipped with uniform light distribution acrylic diffuser.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

嵌入式筒灯，压铸式铝合金外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐性。配备扩散面板(亚克力材质)，实现均匀出光。



Product Name/产品名称	FR3004W			
Dimension/尺寸	ø 115mm*60mm			
Lamp Source/光源	CREE COB (Bridgelux / CITIZEN Optional)			
Wattage/瓦数	12W			
Luminous Flux/光通量	780 Lumen			
Luminaire Efficacy/光效	65 Lumen / Watt			
Color Temperature/色温	2700K	3000K	4000K	6500K
CRI/显色指数	>80 (over 90 optional)			
Dimming Method/调光方式	Triac, 0-10V, Dali			
Beam Angle/光束角	90 °			
Cut Hole Size/开孔尺寸	ø 100mm			
Available Color/外壳颜色	White, Black			
Shell material/外壳材质	Aluminum			
IP Rating/防护等级	IP20			
Certification/证书	CE			

FR3004W