

IURANUS BACKLIGHT



Product Description

Uranus Backlight

"Uranus" backlight system with a patented quick fixing method . Order made to Fit size with high uniformity back light. Extremely quick installation method with simple and clear wiring. All the hinges and wires are upgraded to comply UL-94V0 material standard.

"天王星"背光系统，采用专利快速固定方式。定制适合尺寸，背光高度均匀。极其快速的安装方法，布线简单。所有铰链配件及电线已提升及达到UL-94V0标准。

Product Name/产品名称	Foldable LED Backlit Panel		
Model/型号	GFP1512-12V		
Dimension/尺寸	60mm*6000mm (Max.)		
Lamp Source/光源	Nichia LED NF2W757GR-V3		
Wattage/瓦数	70W per Meter		
Luminous Flux/光通量	~8400 Lumen / m ²		
Luminaire Efficacy/光效	100 Lumen / Watt		
Color Temperature/色温	6500K		
CRI/显色指数	>82		
Dimming Method/调光方式	0-10V		
Beam Angle/光束角	150°		
Cut Hole Size/开孔尺寸	N/A		
Available Color/外壳颜色	White		
IP Rating/防护等级	IP20		
Certification/证书	Certificate	Certificate No.	Test Report No.
	EN 60598-1:2015+AC:2016	BST16098588A0001Y-1SC-2	BST16098588A0001Y-SR-2
	EN 60598-2-1:1989	BST16098588A0001Y-1SC-2	BST16098588A0001Y-SR-2
	EN 55015:2013/A1:2015	BST16098588A0001Y-1EC-1	BST16098588A0001Y-1ER-1
	EN 61547:2009	BST16098588A0001Y-1EC-1	BST16098588A0001Y-1ER-1
	EN 61000-3-2:2014	BST16098588A0001Y-1EC-1	BST16098588A0001Y-1ER-1
	EN 61000-3-3:2013	BST16098588A0001Y-1EC-1	BST16098588A0001Y-1ER-1
	UL94V0 pass for Electrical Cable (252/0.08TS OD=3.0mm)		BST 180911917302ERR
	IEC60695-2-11 pass for Hinge for Uranus		BST 180911917301ERR
	IEC62471(2006)		SQETB18110201L