



Beam Angle (Full): 100°

0.5	1.33	4888
1.0	2.66	1922
1.5	4.00	543
2.0	5.33	306
2.5	6.66	198
3.0	7.99	136



Distance (m) Core Diameter (m) Illuminance (lx)

Product Description

High Lumen pendant luminaire with integrated LED linear light. Installation can be by hanged wires, optional accessories include wires and connecting plastic parts.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

高流明吊灯，安装可以通过吊线，可选配件包括电线和连接塑料部件。



SK5386

Product Name/产品名称	SK5386				
Dimension(WxH)/尺寸	53mm x 86mm				
Dimension(L)/尺寸	0.6m	0.9m	1.2m	1.5m	1.8m
Lamp Source/光源	LED				
Wattage/瓦数	20W	30W	40W	50W	60W
Luminous Flux/光通量	1600 Lumen	2400 Lumen	3200 Lumen	4000 Lumen	4800 Lumen
Luminaire Efficacy/光效	80 Lumen / Watt				
Color Temperature/色温	3000K/4000K/6000K				
CRI/显色指数	>82				
Dimming Method/调光方式	Triac, 0-10V, Dali				
Beam Angle/光束角	80°				
Tilt Angle/可调角度	White Powder Spray as Default				
Shell Material/外壳材质	Aluminum+Polycarbonate			Aluminum+Acrylic	
IP Rating/防护等级	IP20				