



Beam Angle (Full): 100°

0.5	1.32	2730
1.0	2.63	1062
1.5	3.95	303
2.0	5.27	171
2.5	6.59	109
3.0	7.90	79



©2014 MIRON - Data Engineering Dept. - Shenzhen, P.R.C.

Product Description

High Lumen pendant luminaire with integrated LED linear light. Installation can be by hanged wires, optional accessories include wires and connecting plastic parts.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

高流明吊灯。安装可以通过吊线，可选配件包括电线和连接塑料部件。



| SKN32120

Product Name/产品名称	SKN32120				
Dimension(WxH)/尺寸	32mm x 120mm				
Dimension(L)/尺寸	0.6m	0.9m	1.2m	1.5m	1.8m
Lamp Source/光源	LED				
Wattage/瓦数	12W	18W	24W	30W	36W
Luminous Flux/光通量	1200 Lumen	1600 Lumen	2400 Lumen	3200 Lumen	4000 Lumen
Luminaire Efficacy/光效	75 Lumen / Watt				
Color Temperature/色温	3000K/4000K/6000K				
CRI/显色指数	>82				
Dimming Method/调光方式	Triac, 0-10V, Dali				
Beam Angle/光束角	80°				
Available Color/外壳颜色	Sanded White Powder Spray Effect as Default				
Shell Material/外壳材质	Aluminum+Matted Polycarbonate				
IP Rating/防护等级	IP20				