



Product Description

UM5024C:

Magnetic Adsorption Technology , Light , Adjustable downlight with different beam angle(s) with Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . coating 350° adjustable in the horizontal direction and 90° in vertical direction.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

磁性吸附技术导轨系统，固定型筒射灯，可定制不同角度，铝外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐性。可在水平方向旋转350°以及垂直方向旋转90°。

UM5024D:

Magnetic Adsorption Technology , Light , Adjustable Linear light with Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . coating 350° adjustable in the horizontal direction and 90° in vertical direction.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

磁性吸附技术导轨系统，固定型线条灯，铝外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐性。可在水平方向旋转350°以及垂直方向旋转90°。



Product Name/产品名称	UM5024C	UM5024D
Dimension/尺寸	84*50*80mm	204/404/604/804/1004*35*43mm
Lamp Source/光源	LED COB	LED COB
Wattage/瓦数	3W/5W/7W	6W/12W/18W/24W/30W
Luminous Flux/光通量	237lm/395lm/553lm	486lm/972lm/1458lm/1944lm/2430lm
Luminaire Efficacy/光效	>79lm/W	>80lm/W
Color Temperature/色温	3000K/4000K/5700K	3000K/4000K/5700K
CRI/显色指数	>80	>80
Dimming Method/调光方式	Optional	Optional
Beam Angle/光束角	15°	120°
Tilt Angle/可调角度	90°	90°
Rotation Angle/转动角度	350°	350°
Available Color/外壳颜色	White, Black	White, Black
Shell material/外壳材质	Aluminum + Polycarbonate	Aluminum + Polycarbonate
IP Rating/防护等级	IP20	IP20

UM5024C/UM5024D