



### Product Description

#### UM5024E:

Magnetic Adsorption Technology , Light , Adjustable downlight with different beam angle(s) with Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . coating 350° adjustable in the horizontal direction and 90°in vertical direction.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

磁性吸附技术导轨系统，固定型单排射灯，可定制不同角度，铝外壳，先进的粉末喷涂技术，有效提高抗氧化性和防腐蚀性。可在水平方向旋转350°以及垂直方向旋转90°。

#### UM5024F:

Magnetic Adsorption Technology , Light , Pendant fixture(s) with Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

磁性吸附技术导轨系统，垂吊型筒灯，由铝合金制成，配合先进的粉末喷涂技术，有效提高抗氧化性和防腐蚀性。



Product Name/产品名称	UM5024E	UM5024F
Dimension/尺寸	84/163/322/481*35*42mm	240*50*180mm
Lamp Source/光源	LED SMD	LED COB
Wattage/瓦数	3W/6W/12W/18W	3W/5W/7W
Luminous Flux/光通量	246lm/482lm/984lm/1476lm	237lm/395lm/553lm
Luminaire Efficacy/光效	>80lm/W	>79lm/W
Color Temperature/色温	3000K/4000K/5700K	3000K/4000K/5700K
CRI/显色指数	>80	>80
Dimming Method/调光方式	Optional	Optional
Beam Angle/光束角	15°/30°/45°	15°
Tilt Angle/可调角度	90°	/
Rotation Angle/转动角度	350°	/
Available Color/外壳颜色	White, Black	White, Black
Shell material/外壳材质	Aluminum + Polycarbonate	Aluminum + Polycarbonate
IP Rating/防护等级	IP20	IP20