





Reflector Cup Beam Angle (Full): 24°			Lens Beam Angle (Full): 24°		
Distance (ft)	Cone Diameter (ft)	Illuminance (fc)	Distance (ft)	Cone Diameter (ft)	Illuminance (fc)
0.5	0.20	8244	0.5	0.27	11484
1.0	0.39	2061	1.0	0.46	2874
1.5	0.58	916	1.5	0.67	1277
2.0	0.78	515	2.0	0.89	718
2.5	0.98	330	2.5	1.11	460
3.0	1.18	229	3.0	1.33	319

### Product Description

Fired Rated downlight conform BS476-21, match the fire rating of the ceiling, maintaining its minimum period of fire resistance. They are tested for up to 60 minutes of fire resistance, which is enough for most ceilings in most buildings.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.



<b>Product Name</b>	FR1011	
<b>Dimension</b>	ø 90mm*71mm	
<b>Lamp Source</b>	CREE COB (Bridgelux / CITIZEN Optional)	
<b>Wattage</b>	10W	12W
<b>Luminous Flux</b>	790 Lumen	920 Lumen
<b>Luminaire Efficacy</b>	79 Lumen / Watt	76 Lumen / Watt
<b>Color Temperature</b>	2700K, 3000K, 4000K, 5000K	
<b>CRI</b>	>80 (over 90 optional)	
<b>Dimming Method</b>	Triac, 0-10V, Dali	
<b>Beam Angle</b>	24° / 38° / 60°	
<b>Tilt Angle</b>	N/A	
<b>Rotation Angle</b>	N/A	
<b>Cut Hole Size</b>	ø 70mm	
<b>Available Color</b>	White, Black	
<b>Certification</b>	CE	
<b>IP Rating</b>	IP65	

FR1011